

## **SALT GUARD**

### **ANTI EFFLORESCENCE PRIME COAT**

### **DESCRIPTION**

**SALT GUARD** is a specially pigmented coating which acts as an anti-efflorescence primer and prevents the growth of salt formation on the wall.

### **FEATURES**

- Excellent alkali & efflorescence resistances
- Physical barrier to water transport
- Chemical barrier to salt migration
- Excellent substrate penetration & top-coat adhesion

### **BENEFITS**

- Long-life high-class appearance of topcoat
- Less topcoat & re-painting required
- Ideal for high-alkaline concrete
- Prevention of top coat defects

### **TYPICAL APPLICATION**

To be applied over concrete, plastered or brick, masonry surfaces.

### **TYPICAL CHARACTERISTICS**

Nature	: single component, liquid
Color	: Turbid white
Specific gravity at 30 °C	: 1.08 ± 0.04
Inter-coat interval	: 4 to 6 Hrs
Dilution	: 50% potable water
Coverage	: 55-60 sq. ft. per 2 coats/ ltr.
DFT	: 30 40μ

### **DIRECTIONS FOR USE**

Clean the surface with brush and ensure no loose particle remains on the substrate. On the clean and dry substrate apply it with the help of a brush. Application is to be done till saturation level is achieved. Allow it to dry for 1-2 Hrs. then apply second coat and after 24 hrs apply top coating.

### **CLEANING OF TOOLS AND EQUIPMENT**

Tools and equipment can be easily cleaned with water. If dries, it should be scrapped off.

## **SALT GUARD**

### **ANTI EFFLORESCENCE PRIME COAT**

#### **STORAGE AND SHELF LIFE**

- In order to preserve all the properties, store the material in the original un-opened containers in cool and dry place.
- Shelf life is 24 months.

#### **PACKING**

1 lit 4 ltr and 18 ltr.