



Bostik Two in One

INTEGRAL WATERPROOFING / WATER REDUCING ADMIXTURE



DESCRIPTION

Bostik Two in One is a chloride free integral water proofing and water reducing admixture for plaster and concrete

RECOMMENDED USES

Concrete roof slabs
Floor screed in bathroom and damp areas
Basement slabs and walls
Concreting /Plastering of water tanks and sumps
External/Internal plastering

FEATURES & BENEFITS

Increases workability and improves placing & compaction of concrete
Blocks the capillary structure within concrete
Improves durability and compressive strength
Improves cohesion and prevents segregation of concrete
Confirms IS 2645-2003& IS 9103-1999

PERFORMANCE PROPERTIES

Specific gravity	: 1.18- 1.20
pH	: 7.0-9.0
Chloride	: <0.05%

INSTRUCTIONS FOR USE

Dosage

The normal range is 200 ml per 50 kg cement. Trials

should be done to determine the particular requirements for a specific use.

COMPATIBILITY WITH CEMENTS

It can be used with all types of Portland cements

DISPENSING

The addition of Bostik Two in One to dry mix is not recommended .Bostik Two in One can be dosed either at the batching plant or the placing site .At the batching plant, introduce Bostik Two in One at the specified dosage directly into the mixer through dispenser along with mixing water, when concrete is thoroughly wet and mix for at least 2 minutes after addition

CURING

Normal curing is recommended. Bostik CCC, curing membrane or alternative methods such as polythene, water spray or wet hessian should be used.

CLEANING

Spillages of Bostik Two in One can be removed with water.

PACKAGING

Bostik Two in One is supplied in 200 ml, 1, 5, 20 & 200 litre drums.

STORAGE & SHELF LIFE

Bostik Two in One as supplied shall be stored in a cool and dry place away from sunlight, moisture and high

humidity and have a shelf life of 12 months in the original packing.

HEALTH & SAFETY

Bostik Two in One is non-toxic. Any splashes to the skin should be washed immediately with water. Splashes to the eyes should be washed immediately with water and medical advice should be sought.

FIRE

Bostik Two in One is non flammable.

WARRANTY

Whilst Bostik India (P) Ltd., strives to ensure that any advice, information or recommendation given are appropriate and correct, it cannot accept any liability directly or indirectly arising out of the products, since the method and place of application of the products are beyond its control. Its guarantee is therefore limited to the quality of materials delivered

BOSTIK HOTLINE

Smart help +91 80 27833520

Bostik India Private Limited

124 / 1 & 124 / 2A, Kachanayakanahalli, Off. Hosur Road,
Bommasandra Post, Anekal Taluk, Bengaluru – 560 099,
India. E-mail : bostikinfo.india@bostik.com
For more information explore : www.bostik.com



Disclaimer : All representations & recommendations set forth are given in good faith & to the best of our knowledge. However, due to varying conditions & applications, the buyer shall conduct its own tests of this product before use. Under no circumstances will the manufacturer be liable for any loss, damage caused by incorrect usages. The sale of this product shall be on terms & conditions set forth on Bostik's order acknowledgement.