



Exteriorcoat

HIGH PERFORMANCE ACRYLIC COATING



DESCRIPTION

Bostik Exterior Coat is a high performance acrylic based water proofing coating with antifungal and crack bridging ability. Recommended for protection of exterior cementitious surfaces

RECOMMENDED USES

It is an ideal material recommended for

- RCC Structure
- Masonry Walls
- Sloping /Flat Roofs
- Cooling Tower
- Bridges

FEATURES & BENEFITS

- Waterborne product , Eco-friendly
- Single component , ease of application
- Tint able white base
- Excellent antifungal & antibacterial properties
- Low water absorption
- Seamless membrane with good breath ability
- Reliable crack bridging
- Low dirt pick up
- Long term exterior durability
- UV stable

PERFORMANCE PROPERTIES

Type	Single pack
Colour	White
Consistency	Thixotropic liquid
Surface dry time	30 minutes
Adhesion on concrete	Excellent

APPLICATION PROCEDURE

Surface Preparation

Concrete surfaces should be free from laitance, impurities & dust. The pre-requisites for good adhesion of the coating are cleanliness of the surface. Unless these are ensured by proper surface preparation, a successful performance can not be guaranteed.

APPLICATION

Any deficiencies on the surface should be rectified before applying Bostik Sealer coat

Dilute Sealer coat up to 10% by volume with potable water

Apply Sealer coat for better adhesion and sealing

Allow the sealer coat to dry for 2 hours

Dilute Bostik Exterior Coat 20% by volume with potable water

Apply first coat Bostik Exterior Coat by roller or brush on the primed surface

Allow drying for 4-5 hours before application of second coat

CLEANING : Water based product .Hence ease of cleaning all tools by soap water followed by plain water.

COVERAGE

Bostik Sealer coat : 12 sq.m /ltr/coat

Bostik Exteriorcoat: 5.5 sq.m /ltr/2coat @
80 micron DFT

Actual coverage depends on application techniques, ambient conditions, wastage, surface condition etc.

PACKAGING

Bostik Sealer coat : 1 & 5 Ltrs

Bostik Exterior Coat : 5 & 20 Ltrs

STORAGE & SHELF LIFE

Exterior Coat as supplied shall be stored in a cool and dry place away from sunlight, moisture and high humidity and have a shelf life of 12 Months in the original sealed packing.

HEALTH & SAFETY

Exterior Coat is water borne paint & eco-friendly. It is not health hazardous.

BOSTIK HOTLINE

Smart help +91 80 27833520

Bostik India Private Limited

124 / 1 & 124 / 2A, Kachanayakanahalli, Off. Hosur Road,
Bommasandra Post, Anekal Taluk, Bengaluru – 560 099,
India. E-mail : bostikinfo.india@bostik.com
For more information explore : www.bostik.com



Disclaimer : All representations & recommendations set forth are given in good faith & to the best of our knowledge. However, due to varying conditions & applications, the buyer shall conduct its own tests of this product before use. Under no circumstances will the manufacturer be liable for any loss, damage caused by incorrect usages. The sale of this product shall be on terms & conditions set forth on Bostik's order acknowledgement.