



FILL-A-GAP

NON SLUMP FLEXIBLE ACRYLIC GAP SEALANT AND FILLER



DESCRIPTION

Bostik Fill-A-Gap is a one-part water based, paintable acrylic gap filler. It is a general purpose, gun able one-part water based, acrylic gap filler. This easy to use, economical sealant provides excellent adhesion for gaps in low movement joints.

RECOMMENDED USES

Sealing cracks in plasterboard
Sealing window and door frames
Sealing around ceramic tiles
Sealing low movement joints
Crack filling prior to painting
Sealing cracks in brickwork and concrete
Sealing between light partition walls
Sealing skirting and architraves

FEATURES & BENEFITS

Excellent sealing and adhesion properties
Skins within 15 minutes
After 2 hours can be over - painted with acrylic paint
Once fully cured (2-3 days) oil based paint can be used
Interior / Exterior use
High bond strength
Once cured, excellent water resistance

PAINTABILITY

Bostik Fill-A-Gap can be painted over with most types of paint. In most cases Fill - A - Gap can be painted over in 2 hours, this is dependent on gap size and depth. In general larger the gap size longer the drying time

PERFORMANCE PROPERTIES

Typical properties after 7 days cure at 25°C and 50% RH

Appearance	Smooth paste like Consistency
Colour	White
Chemical type	Water based acrylic
Specific Gravity	Approx.1.6
Shore A Hardness	Approx. 80
Tensile Strength (E Modulus 100%)	15 N / cm
Service Temperature	- 20°C to + 75°C
Application temperature	5°C to 80°C
Tool working time	15 minutes at 20°C
Tack free time (skin time)	15 minutes
Full cure	2 - 3 days (depending on Temp)
Max. Joint movement	10%
Maximum Joint Width	up to 25 mm .

COVERAGE

The estimated linear metre yield per pack size is recommended in the following table. No allowance has been made for waste or irregular joint geometry

JOINT SIZE (D x W)	5mm x 5mm	5mm x 10mm	10mm x 10mm	10mm x 20mm
400gms Cartridge	10	5	2.5	1.25
1 kg container	25	12.5	6.25	3.125

Calculation formula : $\frac{W \times D \times L}{1000} = \text{Litres}$

W=Joint width (mm), D=Joint depth (mm), L=Length (metres)

PACKAGING

400 gm cartridge, 1, 5 & 10 kg Containers

STORAGE & SHELF LIFE

Store in a cool dry conditions for a shelf life of 24 months. Store away from oxidising agents and acids.

BOSTIK HOTLINE

Smart help +91 80 27833520



Bostik India Private Limited

124 / 1 & 124 / 2A, Kachanayakanahalli, Off. Hosur Road,
Bommasandra Post, Anekal Taluk, Bengaluru – 560 099, India.
E-mail : bostikinfo.india@bostik.com
For more information explore : www.bostik.com

Disclaimer : All representations & recommendations set forth are given in good faith & to the best of our knowledge. However, due to varying conditions & applications, the buyer shall conduct its own tests of this product before use. Under no circumstances will the manufacturer be liable for any loss, damage caused by incorrect usages. The sale of this product shall be on terms & conditions set forth on Bostik's order acknowledgement.